

# Smart Co-Locate Cab

## Multi-Cell Cabinet

Återförsäljare:

Tre Röda AB

Tillingehagby 7 - 745 94 ENKÖPING

Tel: 08-560 200 22

e-post: [info@treroda.nu](mailto:info@treroda.nu)

<http://www.treroda.nu>

Smart Co-Locate cabinets maximise the available floor space by enabling multiple hosting of equipment in one cabinet footprint, saving cost.

### Benefits and Features

- Highly secure with total separation of individual client cells with through protected wiring available
- High heat loads are cooled by a range of optional fan configurations, with temperature control modules and remote alarms
- Individual customer cells can have independently adjustable 19 inch mounting posts for variable depth equipment within any cell if required
- Reconfigurable structure allows individual door heights and corresponding cell heights to be easily changed at any time
- The server friendly design provides exceptionally versatile cable management, equipment mounting and cooling with robust capability
- Plain security divider panel fitted between each cell
- Security is of the highest order, enhanced with available upgrades for locks and surveillance
- Cannon is able to supply individually paired locks for security. Cabinets may for example have 4 separate locking compartments. Alternative key numbers available
- Cannon electronic locking systems are available for keypad or remote activation, with alarms
- Full environmental control options are available with remote control and management (see CannonGuard)
- Full power management, with sequential switching and power metering, remotely controlled and alarmed is available. Please see CannonGuard for further details
- A high tech and elegant co-locate system to provide a total solution for today and the future
- Mountable on Cannon RAft System for raised floor installation to remove the need for tile cutting
- Will integrate with Cannon overhead Cable Raceway for simplifying overhead cabling
- Extensive cable entry gland positions in roof
- In rack cable pass through external to client cells for maximum cabling security

### Finish

Standard: Powder painted Velvet Black to RAL 9005 or Chameleon (Grey White) to RAL 9002.  
Other colours available on request.



Can be re-configured to alternative cell numbers by purchasing alternative door sets

**Size conversions: 1U = 44.45mm = 1 3/4" 600mm = 24" 700mm = 28" 800mm = 32" 1kg = 2.2lbs**

### Standard specification

- Two heights: 42U and 47U
- Two widths: 600mm and 800mm
- One depth: 1000mm
- Available in 2 cell, 3 cell or 4 cell
- Infinitely adjustable 19-inch mounting posts allowing universal equipment mounting
- Plain (non-vented) security divider panel fitted between each cell
- Two drop-in ribbed and lockable secure side panels
- MaxiVent perforated doors front and rear, supplied with swing-handle key locks. Each cell has different lock/key number
- All doors open 180° when bayed and 270° at end of bay or when stand-alone
- Quick-release hinges on all doors
- Maximum cable access through base, can be blanked off if required
- Four transit castors fitted
- Multiple moulded finger cable entry glands in roof
- Secure Cable Trunking included

### Technical information

- Manufactured (where applicable) to BS.EN60950 2002, IEC 60297, EIA-310-D, UL94V0
- Load rating: 1000kg static (sited directly on floor)

### Order Codes

#### Two (2) Cell Co-Locate

| Description          | Order Code |
|----------------------|------------|
| 42U x 600mm x 1000mm | COL2426099 |
| 47U x 600mm x 1000mm | COL2476099 |
| 42U x 800mm x 1000mm | COL2428099 |
| 47U x 800mm x 1000mm | COL2478099 |

#### Three (3) Cell Co-Locate

| Description          | Order Code |
|----------------------|------------|
| 42U x 600mm x 1000mm | COL3426099 |
| 47U x 600mm x 1000mm | COL3476099 |
| 42U x 800mm x 1000mm | COL3428099 |
| 47U x 800mm x 1000mm | COL3478099 |

#### Four (4) Cell Co-Locate

| Description          | Order Code |
|----------------------|------------|
| 42U x 600mm x 1000mm | COL4426099 |
| 47U x 600mm x 1000mm | COL4476099 |
| 42U x 800mm x 1000mm | COL4428099 |
| 47U x 800mm x 1000mm | COL4478099 |

### Options/Upgrades

- Vented framed steel doors or glass doors
- Vertically split wardrobe doors
- QuickChange zero-U, roof mounted fan unit: 2, 4 or 6 Fans
- Power Distribution Units
- RAfT and Raceway compatible
- AIR-LOKK options
- CannonGuard upgrades available: remote system management/remote access control/high capacity cooling and remote environmental control/remote power management/local condition monitoring - See CannonGuard brochure

### Cabinets fitted with Secure Cable Trunking

800mm wide version shown here



### Earth Bonding Kits

| Description                          | Order Code |
|--------------------------------------|------------|
| Earth Bonding Kit for 2 Cell Cabinet | KP0223-2   |
| Earth Bonding Kit for 3 Cell Cabinet | KP0223-3   |
| Earth Bonding Kit for 4 Cell Cabinet | KP0223-4   |

### Other cell configurations available

Size conversions: 1U = 44.45mm = 1 3/4"    600mm = 24"    700mm = 28"    800mm = 32"    1kg = 2.2lbs