

APPLICATIONS

The COMMSRAK is a low cost easy to use 19" cabling frame in 12 , 37 & 42

Features

- Supplied in configured kit form
- 3 height options - 12 , 37 and 42
- Open frame construction gives all round access
- Cable management provided in verticals
- Assembly tool included
- Load rating 150kg
- **Wide range of 19" Accessories – see below for details**

Contents of kit

Item/Description	Material/Finish
1 COMMSRAK	1,6mm zintec steel, paint RAL 7035

Note: Order frame then floor or wall kit

Ordering information

Description	Order code
12 frame	52-255052B
37 frame	52-255051E
42 frame	52-255050H

Mounting Options

The Commsrak Frame is designed to be either floor or wall mounted. The floor mounting kit includes two heavy duty feet and uses the industry standard 600mm x 600mm footprint. The wall mounting kit consist of 4 x brackets and is available in depths of 285mm or 400mm. Mounting kits are manufactured from 2mm Steel and painted RAL 7035 (Pale Grey)

The following accessories are available for Commsrak:

Baying Kit – Comprising of a simple bracket and fixings used to bay two commsraks together. (Material: 1.2mm Steel, Finish: Painted RAL 7035 - Pale Grey)

Top Cover – Full width and 450mm deep the cover is secured to top of the Commsrak and provides protection to the equipment housed within. (Material: 2mm Steel, Finish: Painted RAL 7035 - Pale Grey)

Earth Kit – Comprises of 4 x leads to electrically bond the vertical and horizontal members of the Commsrak together plus 1 x lead to connect to an Earth point. (ses 4mm Tri-Rated green/yellow cable)

Castors – Supplied as a kit of 4, these light/medium duty castors screw into the floor mounting kits. They and have a static load rating of 65KG each and are available in braked and unbraked versions. (Thread = M10)

Adjustable Feet – For uneven surfaces, a set of 4 x adjustable feet can be used allowing a floor standing commsrak to be correctly aligned. (Thread = M10)

Cantilever Chassis Support – Supplied as a pair, these fix directly onto the vertical members. They can be used to support equipment by themselves or with the chassis tray (below) mounted on them. Nominal load per pair of cantilever chassis supports is 20KG. (Material: 1.6mm Steel, Finish: Zinc plate and passivate)

19" Cantilever Shelf – These shelves are 250mm deep, fix directly to the standard 19" panel mounts and occupy 2 of rack height. Nominal load per shelf is 20KG. (Material: 1.6mm steel, Finish: Painted RAL 7035 Pale Grey)




19" CANTILEVER SHELF




CANTILEVER CHASSIS SUPPORT



WALL AND FLOOR STANDING COMMSRAK



FLOOR STANDING



TOP COVER



FEET AND CASTORS



WALL MOUNTING KIT

Ordering Information

Description	Order code
Floor Mount Kit	52-255053
286mm Wall Mount Kit	52-251177
400mm Wall Mount Kit	52-257133
Baying Kit	52-244931
Top Cover	52-248074
Earth Kit	52-248075
Medium Castors (2braked 2 unbraked)	802-560002
Medium Castors (4 unbraked)	802-561557
Adjustable feet	802-560001
Cantilever Chassis Supports	802-563106
19" Cantilever Shelf	52-4000553

Aterförsäljare:

Tre Röda AB
 Tillingehagby 7 - 745 94 ENKÖPING
 Tel: 08-560 200 22
 e-post: info@treroda.nu
 http: www.treroda.nu

